

MT17 Series



Model		MT17-xxx
LCD Display		17" TFT
Display Size (HxV mm)		337.9 x 270.3
Pixel Pitch (HxV mm)		0.264 x 0.264
Max. Resolution (acceptable)		SXGA 1280x1024
Contrast Ratio		500:1
Brightness		300 cd/m ²
Response Time		8 ms (Typical)
Display Color		162K
Viewing Angle	H/V	+140°~-130°
PC Interface	Video	RGB analog (75Ohms, 0.7Vp-p)
	Sync.	H/V separated (TTL) positive/negative
Audio (Option)		Stereo Mini-Audio Line-In
		2 x 2.5W speakers
Touch Screen		Capacitive Type / Resistive Type (4Wire, 5Wire, 8Wire)
Touch Screen Interface		Serial(RS232)/USB
Digital Interface	Analogue	D-sub 15 Pin (VGA)
	DVI	DVI
Power	Form	Imbedded universal power/ AC/DC Adapter Input AC 100~240V, 50~60Hz, Output DC 12V/3A
	Consumption	40W (MAX.)
Key Controls		Power on/off with LED, Menu, Select, Sdjustment (+,-)
Operating Condition	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-90% (no condensing)
Safety & EMI		UL/CE/FCC/TUV/GS
Dimensions (HxWxD mm)		380 x 383 x 180

*Specifications are subject to change in different panel used.

燦微科技股份有限公司

Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五

TEL : (02) 2698-8072 FAX : (02) 2698-8092

www.transpoint.com.tw

