


# MT22W Series



Model		MT22W-xxx
LCD Display		22" W TFT
Display Size (HxV mm)		473.76 x 296.1
Pixel Pitch (HxV mm)		0.282 x 0.282
Max. Resolution (acceptable)		1680 x 1050 (WSXGA)
Contrast Ratio		1000:1
Brightness		300 cd/m <sup>2</sup>
Response Time		5 ms (gray to gray)
Display Color		16.7M
Viewing Angle	H/V	+160°~-160°
PC Interface	Video	RGB analog (75Ohms, 0.7Vp-p)
	Sync.	H/V separated (TTL) positive/negative
Audio (Option)		Stereo Mini-Audio Line-In
		2 x 2W speakers
Touch Screen		3M-MicroTouch Capacitive Touch / Resistive Touch
Touch Screen Interface		Serial(RS232)/USB
Digital Interface	Analogue	D-sub 15 Pin (VGA)
	DVI	DVI
Power	Form	Imbedded universal power/ AC/DC Adapter Input AC 100~240V, 50~60Hz, Output DC 12V/3A
	Consumption	50W (MAX.)
Key Controls		Power on/off with LED, Menu, Select, Sdjustment (+,-)
Operating Condition	Temperature	0°C-40°C (32°F-104°F)
	Humidity	10%-90% (no condensing)
Safety & EMI		UL/CE/FCC
Dimensions (HxWxD mm)		513.2 x 384.6 x 180.0

\*Specifications are subject to change in different panel used.



燦微科技股份有限公司  
Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五  
TEL : (02) 2698-8072 FAX : (02) 2698-8092

[www.transpoint.com.tw](http://www.transpoint.com.tw)