

O

K-15 Series Touch Monitor



Model	OK15-1MS / OK15-1MU / OK15-5MS / OK15-5MU / OK15-5LS OK15-5LU / OK15-8MS / OK15-8MU / OK15-8LS / OK15-8LU	
LCD Display	304.1mm X 228.1mm	
Pixel Pitch	0.297mm x 0.297mm	
Max. Resolution	1024X768	
Contrast Ratio	400:1	
Brightness	250 cd/m ²	
Response Time	25 ms	
Display Color	16M	
Viewing Angle	L/R	+70°~-70°
	U/D	+70°~-70°
PC Input Interface	R.G.B. Analog (D-Sub 15 PIN)	
Input Signal Frequency	Horizontal: 30~75KHz / Vertical: 50~85Hz	
Power Supply	Input:100~240Vac, 1.5A, 60/50Hz, Universal. Output: 12Vdc, 3.7A.	
Touch Screen(Spec check attach)	3M-MicroTouch Capacitive RS232&USB; 5 Wires Resistive Rs232.	
	3M-DynaPro 8 Wires Resistive RS232& USB	
Touch Monitor Part Number :	X: 1=Capacitive, 5=5 Wires Resistive, 8=8Wires Resistive	
	OK15-XYZ	Y: M= 3M Control Board L= Local Control Board
		Z: S= RS232 Interface U= USB Interface
Dimensions (HxWxD mm)	380mm X 297mm X 48mm	
Weight (net, Kg)	7Kg	
VESA Mounting	None	



燦 微 科 技 股 份 有 限 公 司
Transpoint Technology Inc.

地址：台北縣汐止市新台五路一段77號18樓之5(遠東世界中心大樓B棟)

TEL: +886-2-26988072 FAX: +886-2-26988092

Touch Anywhere You Want