


# OP15 Series



| Model                          | OP15-xxx (Open Frame)                                  |
|--------------------------------|--|
| LCD Display                    | 15"  |
| Pixel Pitch                    | 0.297mm  |
| Display area(mm)               | 304.1 X 228.1  |
| Max. Resolution                | XGA(1024 X 768)  |
| Display color                  | 16.7M COLORS   |
| Contrast Ratio                 | 500 : 1 (Typical )                                     |
| Brightness(cd/m <sup>2</sup> ) | 250 cd/m <sup>2</sup>                                  |
| Response Time(ms)              | 12   |
| Viewing Angle R/L/U/D          | H:140°, V:120°   |
| Input Signal                   | R/G/B Analog   |
| H-frequency (KHz)              | Horizontal: 30 to 80KHz                                |
| V-frequency (Hz)               | Vertical : 50 to 75 Hz                                 |
| Plug & Play                    | DDC 2B   |
| Power Management               | VESA DPMS  |
| Signal type                    | 15 Pin D-sub   |
| AC/DC Adapter                  | Input : AC 100~240, 50~60HZ<br>Output: DC 12V/ 3A      |
| Power onsumption               | 28W  |
| Operation Environment          | Temperature 0~ 40 °C ,<br>Humidity :Less than 85%      |
| OSD Control Button             | Power, Auto, Menu /<br>Enter, Up, Down                 |
| Front panel mounting           | optional   |
| Anti-reflection glass          | optional   |
| Optional                       | S-Video, Video-input                                   |
| Touch panel optional           | Capacitive Type / Resistive Type (4Wire, 5Wire, 8Wire) |

\*Specifications are subject to change in different panel used.



燦徽科技股份有限公司  
Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五  
TEL : (02) 2698-8072 FAX : (02) 2698-8092

[www.transpoint.com.tw](http://www.transpoint.com.tw)