



OP17 Series



Model	OP17-xxx (Open Frame)
LCD Display	17"
Pixel Pitch	0.264mm
Display area(mm)	337.9 X 270.3
Max. Resolution	SXGA(1280 X 1024)
Display color	16.7M COLORS
Contrast Ratio	500 : 1 (Typical)
Brightness(cd/m 2)	300 cd/m 2
Response Time(ms)	8
Viewing Angle R/L/U/D	H:140°, V:130°
Input Signal	R/G/B Analog
H-frequency (KHz)	Horizontal: 30 to80KHz
V-frequency (Hz)	Vertical : 50 to 75 Hz
Plug & Play	DDC 2B
Power Management	VESA DPMS
Signal type	15 Pin D-sub
AC/DC Adapter	Input : AC 100~240, 50~60HZ Output: DC 12V/ 3A
Power onsumption	30W
Operation Environment	Temperature 0~ 40 °C , Humidity :Less than 85%
OSD Control Button	Power, Auto, Menu / Enter, Up, Down
Front panel mounting	optional
Aiti-reflection glass	optional
Optional	S-Video, Video-input
Touch panel optional	Capacitive Type / Resistive Type (4Wire, 5Wire, 8Wire)

*Specifications are subject to change in different panel used.



燦徽科技股份有限公司
Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五
TEL : (02) 2698-8072 FAX : (02) 2698-8092

www.transpoint.com.tw