


RA19 Series



Model	RA19-xxx (Chassis)
LCD Display	19"
Pixel Pitch	0.294
Max. Resolution	1280 X 1024 SXGA
Display color	16.7M COLORS
Contrast Ratio	700:1
Brightness(cd/m ²)	300
Response Time(ms)	8
Viewing Angle R/L/U/D	H:150°, V:135°
Input Signal	R/G/B Analog
H-frequency (KHz)	30 - 80
V-frequency (Hz)	50 - 75
Plug & Play	DDC 2B
Power Management	VESA DPMS
Signal type	15 Pin D-sub
AC/DC Adapter	Input : AC 100~240, 50~60HZ; Output: DC 12V/ 3A
Power onsumption	30W
Operation Environment	Temperature 0~ 40 °C , Humidity :Less than 85%
OSD Control Button	Power, Auto, Menu / Enter, Up, Down
Optional	S-Video, Video-input
Dimension (WxHxD)(mm)	464 X 385 X 46
Weight G.W.(kg)	8.5
LCD Bracket	Optional
Color optional	White/Black
Anti-rflection filter	Optional
Touch panel optional	Capacitive Type / Resistive Type (4Wire, 5Wire, 8Wire)

*Specifications are subject to change in different panel used.



燦微科技股份有限公司
Transpoint Technology Incorporated.

台北縣汐止世新台五路一段77號18樓之五
TEL : (02) 2698-8072 FAX : (02) 2698-8092

www.transpoint.com.tw